

Clarification Request

References: “e.g” [Specified Tests 18.1.Final and BTL Specified Tests-20.0 final.pdf](#)

Date of BTL-WG Response: 2022-02-24

Background: “e.g”_” [Specified Tests 18.1.Final and BTL Specified Tests-20.0 final.pdf](#)

From IPv6 test:

This is regarding the test BTL - 12.X.2.1.5 Execute Forwarded-Address-Resolution.

Purpose: To verify that an IUT, operating in normal IPv6 mode, will process a Forwarded-Address-Resolution message.

Test Concept: The TD, acting as a BBMD, sends a Forwarded-Address-Resolution message to the IUT on behalf of device D2. It is verified that the IUT responds to D2 with an Address-Resolution message.

Test Step:

1. TRANSMIT DA = IUT, SA = TD,
Forwarded-Address-Resolution,
Original-Source-Virtual-Address = D2,
Target-Virtual-Address = IUT
Original-Source-B/IPv6-Address = D2
2. RECEIVE
DA = D2, SA = IUT
Address-Resolution-ACK,
Source-Virtual-Address = IUT,
Destination-Virtual-Address = D2

Our Understanding:

BBMD will never unicast Forwarded-Address-Resolution to device which is not registered in it.

As, IUT is in normal mode, BBMD cannot send unicast Forwarded-Address-Resolution to IUT.

Instead BBMD should broadcast the Forwarded-Address-Resolution in its network.

Also, we feel that IUT should be in same network as that of BBMD. As, BBMD will broadcast the Forwarded-Address-Resolution, then only IUT will receive the request and will respond with ACK.

Question:

1. **Step 1 needs to be changed as:**

TRANSMIT DA = [IUT B/IPv6 Multicast Address](#), SA = TD,
Forwarded-Address-Resolution,
Original-Source-Virtual-Address = D2,
Target-Virtual-Address = IUT

Original-Source-B/IPv6-Address = D2

-
2. Test configuration needs to be added mentioning: *IUT and BBMD should be in same domain.*

RESPONSE:

1. YES
2. YES